

INTERLIN PRODUCT SHEET

New Holland T6030

Price: 15000 €

Rental Cost: 0 € / Per Month



Stock Number	PR-LAP7B
Model	New Holland T6030
Year	2008
Operating Hours	3008 hours
Engine Type	4 cylinders, Diesel, turbo
Displacement	4.5 L
Power	125 hp (92 kW)
Max Torque	510 Nm
Transmission	24 forward gears + 12 reverse gears
Max Speed	40 km/h
Weight	5,350 kg
Fuel Tank Capacity	180 L
Front Tire Dimensions	420/70R28
Front Tire Wear	10%
Rear Tire Dimensions	520/70R38
Rear Tire Wear	10%
Overall Length	4,635 mm
Overall Width	2,355 mm
Overall Height	2,650 mm
Wheelbase	2,440 mm
Ground Clearance	450 mm
Front Lift Capacity	2,400 kg
Rear Lift Capacity	5,500 kg
Hydraulic Flow Rate	120 L/min
Hydraulic Pumps	1 piston pump + 1 gear pump
Number of Valves	4

Available Options:

1. Cab:

- **Deluxe cab** with air conditioning and heating
- **Suspended front axle** for improved stability
- **Ergonomic seat** with suspension and adjustable features

2. Hydraulic System:

- **Advanced hydraulic system** with remote control valves
- **Front and rear linkage** for easy attachment of implements
- **Electro-hydraulic control** for precise lifting

3. Transmission:

- **24-speed transmission** for seamless gear shifts

- **Powershift transmission** (optional) for enhanced efficiency

4. Axles and Tires:

- **Heavy-duty front and rear axles** designed for tough agricultural tasks
- **Variable tire pressure system** (optional) for enhanced traction and soil preservation

5. Electronic Control System:

- **ISOBUS** compatible for modern farming equipment
- **Advanced GPS guidance system** (optional) for improved precision and field mapping

6. Power Take-Off (PTO):

- **Rear PTO** with **540/1000 rpm selector** (standard)
- **Front PTO** (optional)

7. Braking and Safety:

- **Hydraulic wet disc brakes** for reliable stopping power
- **Automatic parking brake** with safety features

8. Steering System:

- **Power steering** for easy maneuverability

9. Comfort Features:

- **Radio** and **CD player** for entertainment
 - **Adjustable armrests** and **controls** for improved operator comfort
-